

Note on re-establishing a TCP connection with the Ether-Serial Link

The nature of TCP socket connections means that a TCP socket established with a host will hold that TCP socket "open" even when active communication has been broken. This situation might occur, for example, when an Ether-Serial Link serial port is connected in Raw Server mode with a host PC that is rebooted without the TCP connection to the Ether-Serial Link being properly closed. While the TCP connection continues to be held open, further TCP connections cannot be established. This "lockout" is normal TCP behaviour designed to allow communications to be smoothly re-established between a TCP client and server.

In the circumstance where connection to an Ether-Serial Link is broken, it may be desirable to allow another client to access the Ether-Serial Link port. To prevent a "lock-out" from persisting, the Ether-Serial Link monitors the TCP port for an active and valid connection every time that a TCP connection request is attempted.

If the connection between the Ether-Serial Link and a client has been "broken," then the next client attempting to connect to the serial port will need to make **two** attempts to connect. The first attempt will cause the Ether-Serial Link firmware to check for the validity of the previously-established TCP connection. If the connection is determined to be "broken," then the Ether-Serial Link will "properly" close the TCP socket. At that point a second connection attempt can be accepted and set up as a new TCP socket. The time interval between connection attempts should be in the order of about 10 seconds.

Note for application programmers: When writing connection code, make the attempt to connect several times, in the event that the previous TCP connection with the Ether-Serial Link serial port was not closed properly under TCP rules.